


delivering solutions since 1946



PANELUX[®]

SOLID ALUMINIUM PANEL

Product Brochure

mulfordplastics.co.nz

PANELUX[®]

SOLID ALUMINIUM PANEL

The Advantages of the PaneLux[®] Series

- Flat panels with different colours, including wooden & marble
- Perforated panels in custom designs in flat panel form or in ready-to-install panels
- Curved and folded panels based on the design requirements

Advantages of Pre-Painted Solid Sheet over Post Painted Solid Aluminium Panels:

Colour Consistency

High quality PVDF coating on a continuous coating line instead of batch by batch coating per panel post fabrication

Perfect Flatness on the facade

Fabrication of panels in-house, ensuring the high quality fabrication and accessories used thereby no compromise on the aesthetics and eliminating chances of errors or risks

Uniform Paint Thickness

Coating process controlled by precise mechanical processes leads to a more uniform paint thickness

Eco-Friendly Production Process

The waste gas produced in the coating process being effectively collected



Colours

Stock



White



Silver



Black



Black Galaxy



Metallic Dark Grey

Indent Solid




Pure White



Milk White




Ivory White



Silver Grey




Moonlight Grey



Grey



Jet Black



Matt Black



Stone Black



Dark Blue



Champagne



Moss Green



Mail Green



Jade Green



Copper Brown



Gold



Light Yellow

Metallic



Metallic Grey



Metallic Champagne



Metallic Silver



Metallic Brass



Metallic Copper



Metallic Matt Gold



Golden Black



Metallic Jade



Metallic Pink

PaneLux[®] Technical Properties

| Technical Properties | PaneLux [®] |
|-----------------------|--|
| Alloy/Temper | 3003H24 |
| Paint System | 2 layer roller coated PVDF |
| Standard Thickness | 3mm (Tolerance +/- 0.15mm) |
| Standard Width | 1550mm (Tolerance ±2mm) |
| Standard Length | ≤6000mm (Tolerance +/-6mm) |
| Panel Weight | 5.4/6.75/8.1kg/m ² |
| Tensile Strength | 145-195 Mpa |
| Coating Thickness | ≥26 microns |
| Warranty [#] | 15 Years (colour) - 20 Years (black/white) |

Lead Time 12 Weeks, Indent Orders[±]
MOQ 1000 square metre per colour[%].

[#]Terms & Conditions Apply.

^{**}Images for Illustration purposes only. Colours may vary from images depicted - images and colours are to be used as a guide only.

[±]Subject to Colour Approval.

[%]Lower quantity may be available, subject to surcharge.

PANELUX[®]

SOLID ALUMINIUM PANEL

Contact Us!

Auckland | Hamilton | Christchurch | Wellington

0800 MULFORD (685 3673)

